

# Fiber Optic Modem VCH-608

 [vremya-ch.com/index.php/en/products-en/signgen-en/vch-608-en/index.html](http://vremya-ch.com/index.php/en/products-en/signgen-en/vch-608-en/index.html)



Fiber-optic modem VCH-608 is designed for receiving and transmitting signals of atomic clocks through a fiber optic communication line (FOCL).

The signals are:

- 1 PPS with delay compensation can be shifted with 100ps step;
- sine 5, 10, 100 MHz with phase instability compensation.

Reception/transmission of high precision signals via the FOCL is provided using a pair of modems: one is configured as a Transmitter and installed at the end of the FOCL where the signal source is located,

the second – as a Receiver and installed at the opposite end of the FOCL. To extend the distance, modified VCH-608 can be used as repeaters. One, two or four fibers can be used for time and frequency transfer, depending on modem modification.

## Key applications:

- metrology;
- time scale comparison systems;
- production and testing of high precision oscillators and devices based on them;
- scientific research.

## Specifications

The optical characteristics of the modem correspond to Class 1 of laser safety, according to IEC 60825-2-2013. The permissible loss of optical power in the FOCL between modems is 25 dB (corresponds to the length of the optical fiber 70 – 110 km).

The type of optical connectors is FC/APC.

## Input electrical signals:

- sinusoidal: 5, 10, 100 MHz, root mean square (RMS) voltage value —  $(1 \pm 0.2)$  V at a load of 50  $\Omega$ ;
- pulse: 1 PPS, amplitude  $\geq 2.5$  V at a load of 50  $\Omega$ , pulse duration —  $(15 \pm 5)$  microseconds, front duration  $< 3$  ns, polarity – positive.

## Output electrical signals:

- sinusoidal: 5 MHz, 10 MHz, 2.048 MHz, 100 MHz, RMS voltage value —  $(1 \pm 0.2)$  V at

a load of 50  $\Omega$ ;

– pulse: 1PPS, amplitude  $\geq 2.5$  V at a load of 50  $\Omega$ , pulse duration —  $(15 \pm 5)$  microseconds, front duration  $< 3$  ns, polarity – positive.

### **Metrological characteristics**

<b>Averaging time, <math>\tau</math></b>	<b>Allan deviation noise floor</b>
1 s	$8.0 \cdot 10^{-14}$
10 s	$1.0 \cdot 10^{-14}$
100 s	$2.0 \cdot 10^{-15}$
1 hour	$1.0 \cdot 10^{-16}$

The error of synchronization when transmitting 1 PPS time signal is no more than 200 ps.  
Dimensions (H×W×D) – 140×483×328 mm.